

LIQUIDLINE®

Oasis Water Cooler

Stylish
contemporary
design with
removable
reservoir for
easy cleaning.



The Oasis indoor water cooler dispenses up to six litres of chilled drinking water every hour. Your whole team can enjoy drinking water of below 10 degrees Celsius.

Contact

0800 8499110
sales@liquidline.co.uk
www.liquidline.co.uk

OASIS

- Depth
13 1/8"
- Weight
45-50lbs



FEATURES

- Stylish design fits well in contemporary kitchen and break room decors
- Scratch-resistant, heavy-duty, durable polycarbonate cabinet
- Patented, easy to clean, dishwasher safe, scratch-resistant removable reservoir
- Patented inside/out cooling probe for dependable water cooling
- Easy to service two piece hot tank (Hot 'N Cold model)
- Large, durable, blue drip tray
- Patented WaterGuard® system eliminates spills during bottle changes and reduces the chance for dust and dirt to enter the cooler reservoir
- 5-year limited warranty

WARRANTY

Limited 5 year warranty (within the Continental Limits of the United States and Canada). Five years on the sealed refrigeration system, one year on most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

For more information or to arrange a tasting either at your premises or in our showroom, call us today.

CABINET

One-piece, heavy-duty textured polycarbonate cabinet, designed to conceal scratches. Pre-drilled holes allow for simple cup dispenser installation.

COLD WATER REFRIGERATION UNIT

Convection cooled condenser. Internal, spring mounted, hermetically sealed compressor with automatic overload protector requires no lubrication. Refrigerant is controlled by a capillary tube.

COLD WATER THERMOSTAT

Temperature is controlled by an adjustable thermostat and easily accessible on the rear of the unit.

COLD WATER RESERVOIR

Durable heavy-duty plastic removable reservoir with refrigerated molded probe that chills water.

TWO PIECE HOT WATER TANK

500 watt easy to service heating element. Hot tank is a type 300 series stainless steel and can be easily opened for cleaning and removal of mineral deposits. Individual components can be replaced when needed, minimizing the need to replace the entire hot tank.

HOT WATER CAPACITY

45 x 6oz. cups of piping hot water per hour. 1½ quart storage tank.

HOT WATER THERMOSTAT

Adjustable thermostat with safety limiter.

HOT WATER SAFETY FAUCET

Self-closing activation requires a two-step action that's easy for adults to use, but protects small children.

DRIP RECEPTOR

Durable drip tray lifts out for easy removal and is dishwasher safe.

ELECTRICAL

115 volts, 60 Hertz. 1/20 hp water cooler compressor. Three wire service cord and polarized plug.

LEAD FREE

Components in this water cooler are lead-free as defined by the Safe Drinking Water Act Amendments of 1986 and the Lead Contamination Control Act of 1988. Model Listed by Underwriter's Laboratories to U.S. and Canadian Standards.