



G10 As versatile, as your beans

Engineered to be timeless

The machines in the G10 range are elegant and solid, with a sophisticated design that draws attention to them. A wide range of models means that you will always find a machine that perfectly suits your needs.

We have combined our heritage of building first-class espresso machines with creative solutions and the latest innovative technology to ensure that all G10 machines deliver what they promise.

That is, a perfectly brewed espresso to your guests. Every day, year after year. G10 fits in all types of environments, from small neighbourhood cafés to top class restaurants.



Features

- Built-in volumetric motor pump, equipped with two retention valves and solid particle filter
- · Copper boiler with pressure relief valve
- Boiler drain tap (except compact)
- Group head with direct pre-infusion chamber
- Stainless steam arms
- Automatic back flush program
- 4 programmable doses settings
- · Heating element thermal cut off

Display Features

- Advertising display
- Coffee audit trail
- Daily machine on/off program
- Precision PID boiler control
- Grind quality alarms
- Service period notification
- Water filter change alarm

Supplied Accessories

- 1 single portafilter all machines
- 2 group, 2 double portafilters
- 3 group, 3 double portafilters
- 0.55 metre water filter hose
- 1.5 metre waste hose
- 1 cleaning membrane
- 1 espresso cup stand

Optional Accessories

· Capsule conversion kits



Details



Variants



1 Group



2 Group Compact



2 Group



2 Group Multi Boiler



3 Group



| Specifications | 1 group | 2 group compact | 2 group |
|-----------------------|----------------------------------|----------------------------------|----------------------------------|
| Height | 20.86 in / 530mm | 20.86 in / 530mm | 20.86 in / 530mm |
| Depth | 23.22in / 590mm | 23.22in / 590mm | 23.22in / 590mm |
| Width | 18.11 in / 460mm | 18.11 in / 460mm | 26.77 in / 680mm |
| Weight | 79 lb / 36 kg | 88 lb / 40 kg | 121 lb / 55 kg |
| Brewing Groups | 1 | 2 | 2 |
| Boiler Volume (Litre) | 6 | 6 | 11.5 |
| Boiler Pressure (Bar) | 0.8 to 1.2 | 0.8 to 1.2 | 0.8 to 1.2 |
| Total Boilers | 1 | 1 | 1 |
| Steam Wands | 1 | 2 | 2 |
| Hot Water Tap | 1 | 1 | 1 |
| Multi Boiler | No | No | No |
| Noise Level | <70dB | <70dB | <70dB |
| Power Supply | 220-240VAC, 50/60Hz, 1N-2770W | 220-240VAC, 50/60Hz, 1N-2780W | 220-240VAC, 50/60Hz, 1N-3330W |
| Water Connection | G3/8 Internal thread | G3/8 Internal thread | G3/8 Internal thread |

| | 2 group multi boiler | 3 group single phase | 3 group three phase |
|-----------------------|----------------------------------|----------------------------------|----------------------------------|
| Height | 20.86 in / 530mm | 20.86 in / 530mm | 20.86 in / 530mm |
| Depth | 23.22in / 590mm | 23.22in / 590mm | 23.22in / 590mm |
| Width | 26.77 in / 680mm | 38.58 in / 980mm | 38.58 in / 980mm |
| Weight | 132 lb / 60 kg | 160 lb / 73 kg | 160 lb / 73 kg |
| Brewing Groups | 2 | 3 | 3 |
| Boiler Volume (Litre) | 11.5 + 1.5 + 1.5 | 17.5 | 17.5 |
| Boiler Pressure (Bar) | 0.8 to 1.2 | 0.8 to 1.2 | 0.8 to 1.2 |
| Total Boilers | 3 | 1 | 1 |
| Steam Wands | 2 | 2 | 2 |
| Hot Water Tap | 1 | 1 | 1 |
| Multi Boiler | Yes | No | No |
| Noise Level | <70dB | <70dB | <70dB |
| Power Supply | 220-240VAC, 50/60Hz, 1N-3330W | 220-240VAC, 50/60Hz, 1N-4290W | 380-415VAC, 50/60Hz, 3N-6290W |
| Water Connection | G3/8 Internal thread | G3/8 Internal thread | G3/8 Internal thread |



Welbilt offers fully-integrated kitchen systems and our products are backed by KitchenCare® aftermarket parts and service. Welbilt's portfolio of award winning brands includes Cleveland™, Convotherm®, Crem®, Delfeld ®, ftkitchen ®, Frymaster®, Garland®, Kolpak®, Lincoln™, Manitowoc ®, Merco®, Merrychef® and Multiplex®.

Bringing innovation to the table \cdot welbilt.com