# Swing Range





### Design and user interface

- Elegant and uncluttered design.
- Capacitive keyboard and wide graphical display.
- LED lighting of the white cell for a maximum visibility of the displayed products.



### Maximum flexibility

- Up to 7 trays which can be easily moved thanks to Vertical Flex (V-Flex)
- Space optimization inside the cell.
- With two optional Visioshop trays it is possible to create a special area for products with non standard packaging, such as salads and ready to go meals.
- Enhanced ETL trays.
- Wider delivery bin.



### High energy efficiency

- C class according to EN 50597 scale.
- Perfect insulation of the cabinet.
- Cooling unit with R290 gas.
- High energy efficieny and dramatic decrease of pull down time.
- Swing can manage up to three temperatures inside the cell or can be set with a 100% Food or Ambient layouts.



An elegant and

High visibility cell



**Swing Range** 








## **Energy consumption**

### **Features** Height 1830 mm 900 mm Width 790 mm Depth Weight 300 kg ca.




### **Electronics**

- Swing is compatible with Newis solutions.
- With Breasy it is possible to select and pay for your product in a completely touchless mode.
- With AmiClo it is possibile to set up the machine remotely.



labels



necta.evocagroup.com



Via Roma 24, 24030 Valbrembo (BG) Italia Tel. +39 035 606111 - Fax +39 035 606519







